

Eclat



Pre-cut Glazing
Apertures

Glazing Apertures
Line Through
With Depression
Mouldings

**PAS 24 2016
Compliant**





Flush Fitted Innerframe.
Unique Integral Flush
Fitting Glazing System
With One Piece Internal
Glass Retention Bead


Patent Pending

Manufactured from Thermoset GRP (Glass Reinforced Polyester), the doors are compression moulded to give a high-definition panel design with the character of timber. The stiles and rails are composed of water-resistant polymer which is bonded to the skin and filled with an insulating core of 100% CFC-free polyurethane.

**DISTINCTION
STANDARD
COLOURS:**



DOOR SPECIFICATIONS:



Structural Dimensions					Trimmability		
Blank Size	A	X	Y	Z	Top	Sides (each)	Bottom
762 x 2013mm	89.2mm	45mm	25mm	-	40mm	30mm	70mm
838 x 2013mm	127.2mm	55mm	35mm	20mm	40mm	40mm	70mm
914 x 2013mm	165.2mm	55mm	35mm	20mm	40mm	40mm	70mm

A = vertical stiles, X = polymer vertical rails, Y = vertical LVL timber, Z = timber lock block.

Parameters guidance

- nxt-gen NXG-EC01 Eclat door blank – maximum / minimum widths 914mm – 722mm using a 45mm B/set lock.
- It is possible to reduce the minimum width by a further 20mm to 702mm when using a 35mm b/set lock, providing your outer-frame rebate leg does not exceed 20mm and handle back plate does not exceed 30mm.

**DISTINCTION
BESPOKE
COLOURS:**



Glass size recommendation

- Top: R275 x 250mm x 24mm unit up to 26.8mm unit.
- Middle: 207mm x 550mm x 24mm units up to 26.8mm units.
- Please refer to Distinction Doors glazing guide.