

Classical Half Glazed



Pre-cut Glazing
Apertures

Glazing Apertures
Line Through
With Depression
Mouldings

**PAS 24 2016
Compliant**




Flush Fitted Innerframe.
Unique Integral Flush
Fitting Glazing System
With One Piece Internal
Glass Retention Bead

Patent Pending


NXG-CL03 Classical Half Glazed

Manufactured from Thermoset GRP (Glass Reinforced Polyester), the doors are compression moulded to give a high-definition panel design with the character of timber. The stiles and rails are composed of water-resistant polymer which is bonded to the skin and filled with an insulating core of 100% CFC-free polyurethane.

**DISTINCTION
STANDARD
COLOURS:**



DOOR SPECIFICATIONS:



Structural Dimensions					Trimmability		
Blank Size	A	X	Y	Z	Top	Sides (each)	Bottom
762 x 2013mm	95.3mm	45mm	25mm	-	40mm	30mm	70mm
838 x 2013mm	133.3mm	55mm	35mm	20mm	40mm	40mm	70mm
914 x 2013mm	171.3mm	55mm	35mm	20mm	40mm	40mm	70mm

A = vertical stiles, X = polymer vertical rails, Y = vertical LVL timber, Z = timber lock block.

Parameters guidance

- nxt-gen NXG-CL03 Classical Half Glazed door blank – maximum / minimum widths 914mm – 712mm using a 45mm B/set lock.
- It is possible to reduce the minimum width by a further 10mm to 702mm when using a 35mm b/set lock, providing your outer-frame rebate leg does not exceed 20mm and handle back plate does not exceed 30mm.

**DISTINCTION
BESPOKE
COLOURS:**



Glass size recommendation

- Top: 202mm x 154mm x 24mm units up to 26.8mm units.
- Middle: 203mm x 574mm x 24mm units up to 26.8mm units.
- Please refer to Distinction Doors glazing guide.